MIP & SMD FC

XF+ 1.2 MIP

Option ID 1005 · XF+ · 1.25 mm pitch



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

OPTICAL & PERFORMANCE

LED technology	**MIP**
Pixel pitch	**1.25 mm**
LED package	**1010**
Brightness	**1000 nit**
Refresh rate	**7680 Hz**
Max frame rate	**240 Hz**
Colour processing	**26 bit**
Scan direction	**horizontal**
Viewing angle H / V	**160° / 160°**

MECHANICAL

Cabinet (W x H x D)	**600 x 337.5 x 38 mm**
Cabinet resolution	**480 x 270 px**
Cabinet area	**0.2025 m²**
Cabinet weight	**8.5 kg**
Cabinet material	**Die-Cast**
Power max / typ.	**480 / 250 W/m²**
Heat dissipation	**1,638 BTU/h/m²**
IP rating	**IP30**
Condition	**indoor**

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	**-10°C~+60°C**
Storage temperature	**-10°C~+40°C**
Working humidity	**10~85%RH**
AC input	**100V~240V, 50~60 Hz**
Typical lifetime	**100000 h**
Certifications	**Pantone** **Pantone Skin Tone** **DICOM**
LED configuration	**Common Cathode**
Bond wire	**None (Flip Chip)**