COB

XF+ 0.9 Power Redundancy

Option ID 1017 · XF+ · 0.94 mm pitch



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

OPTICAL & PERFORMANCE

LED technology	**COB**
Pixel pitch	**0.9375 mm**
LED package	**0407**
Brightness	**1000 nit**
Refresh rate	**3840 Hz**
Max frame rate	**60 Hz**
Colour processing	**26 bit**
Scan direction	**vertical**
Viewing angle H / V	**170° / 150°**

MECHANICAL

Cabinet (W x H x D)	**600 x 337.5 x 28 mm**
Module (W x H)	**150 x 168.75 mm**
Cabinet resolution	**640 x 360 px**
Cabinet area	**0.2025 m²**
Cabinet weight	**4.7 kg**
Cabinet material	**Die-Cast**
Power max / typ.	**430 / 215 W/m²**
Heat dissipation	**1,467 BTU/h/m²**
IP rating	**IP40**
Condition	**indoor**

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	**-10°C~+60°C**
Storage temperature	**-10°C~+40°C**
Working humidity	**10~85%RH**
AC input	**100V~240V, 50~60 Hz**
Typical lifetime	**100000 h**
Certifications	**Pantone** **Pantone Skin Tone**
LED configuration	**Common Cathode**
Bond wire	**Wireless**