

SMD

# XF+ 1.2

Option ID 211 · XF+ · 1.25 mm pitch



REAR / SIDE PICTURES:



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

## OPTICAL & PERFORMANCE

|                     |             |
|---------------------|-------------|
| LED technology      | SMD         |
| Pixel pitch         | 1.25 mm     |
| LED package         | 1010        |
| Brightness          | 800 nit     |
| Refresh rate        | 3840 Hz     |
| Max frame rate      | 120 Hz      |
| Colour processing   | 26 bit      |
| Scan direction      | horizontal  |
| Viewing angle H / V | 160° / 140° |

## MECHANICAL

|                     |                     |
|---------------------|---------------------|
| Cabinet (W x H x D) | 600 x 337.5 x 38 mm |
| Module (W x H)      | 150 x 168.75 mm     |
| Cabinet resolution  | 480 x 270 px        |
| Cabinet area        | 0.2025 m²           |
| Cabinet weight      | 8.5 kg              |
| Cabinet material    | Die-Cast            |
| Power max / typ.    | 650 / 350 W/m²      |
| Heat dissipation    | 2,218 BTU/h/m²      |
| IP rating           | IP30                |
| Condition           | indoor              |

**ELECTRICAL, ENVIRONMENTAL & COMPLIANCE**

|                     |                                               |
|---------------------|-----------------------------------------------|
| Working temperature | <b>-10°C~+60°C</b>                            |
| Storage temperature | <b>-10°C~+40°C</b>                            |
| Working humidity    | <b>10~85%RH</b>                               |
| AC input            | <b>100V~240V, 50~60 Hz</b>                    |
| Typical lifetime    | <b>100000 h</b>                               |
| Certifications      | <b>Pantone<br/>Pantone Skintone<br/>DICOM</b> |
| LED configuration   | <b>Common Anode</b>                           |
| Bond wire           | <b>Copper</b>                                 |