

COB

XF+ 0.7 COB FC

Option ID 403 · XF+ · 0.78 mm pitch



REAR / SIDE PICTURES:



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

OPTICAL & PERFORMANCE

LED technology	COB
Pixel pitch	0.7813 mm
LED package	0407
Brightness	1000 nit
Refresh rate	3840 Hz
Max frame rate	60 Hz
Colour processing	26 bit
Scan direction	vertical
Viewing angle H / V	170° / 150°

MECHANICAL

Cabinet (W x H x D)	600 x 337.5 x 28 mm
Module (W x H)	150 x 168.75 mm
Cabinet resolution	768 x 432 px
Cabinet area	0.2025 m²
Cabinet weight	4.7 kg
Cabinet material	Die-Cast
Power max / typ.	450 / 225 W/m²
Heat dissipation	1,535 BTU/h/m²
IP rating	IP40
Condition	indoor

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	-10°C~+60°C
Storage temperature	-10°C~+40°C
Working humidity	10~85%RH
AC input	100V~240V, 50~60 Hz
Typical lifetime	100000 h
Certifications	Pantone Pantone Skintone
LED configuration	Common Cathode
Bond wire	Wireless