


IMD

XR+ 2.6

Option ID 456 · XR · 2.60 mm pitch



XR+ 500 X 500 MM CABINET: MODULE, DIE-CAST FRAME AND SIDE PROFILE

OPTICAL & PERFORMANCE

LED technology	IMD
Pixel pitch	2.6 mm
LED package	Standard
Brightness	1200 nit
Refresh rate	7680 Hz
Max frame rate	240 Hz
Colour processing	26 bit
Scan direction	Horizontal
Viewing angle H / V	160° / 140°

MECHANICAL

Cabinet (W x H x D)	500 x 500 x 80 mm
Module (W x H)	250 x 250 mm
Cabinet resolution	192 x 192 px
Cabinet area	0.25 m²
Cabinet weight	7.8 kg
Cabinet material	Die-Cast
Power max / typ.	560 / 168 W/m²
Heat dissipation	1,911 BTU/h/m²
IP rating	IP45
Condition	indoor

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	-20...+60 °C
Storage temperature	40°C~+60°C
Working humidity	10~90%
AC input	100~240, 50~60 Hz
Typical lifetime	100000 h
Certifications	DICOM
LED configuration	Common Anode
Bond wire	Copper wire