

MIP & SMD FC

XF+ 1.2 FC

Option ID 524 · XF+ · 1.25 mm pitch



REAR / SIDE PICTURES:



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

OPTICAL & PERFORMANCE

LED technology	SMD FC (GOB)
Pixel pitch	1.25 mm
LED package	1010
Brightness	2500 nit
Refresh rate	7680 Hz
Max frame rate	240 Hz
Colour processing	26 bit
Viewing angle H / V	160° / 160°

MECHANICAL

Cabinet (W x H x D)	600 x 337.5 x 38 mm
Cabinet resolution	480 x 270 px
Cabinet area	0.2025 m ²
Cabinet weight	8.5 kg
Cabinet material	Die-Cast
Power max / typ.	480 / 250 W/m ²
Heat dissipation	1,638 BTU/h/m ²
IP rating	IP30
Condition	indoor

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	-10°C~+60°C
Storage temperature	-10°C~+40°C
Working humidity	10~85%RH
AC input	100V~240V, 50~60 Hz
Typical lifetime	100000 h
LED configuration	Common Cathode
Bond wire	None (Flip Chip)